PRIME
:STAINLESS:

PRIME:STAINLESS: SPECIFICATIONS

SHOWER TRAY

One-piece, 1.5mm thick stainless-steel. Brush-Finish #4
High-density foam supported underside

STANDARD SIZES
Corner and Alcove Tray -- 900 x 900, 1000 x 1000, 1200 x 900, 1200 x 1000,
1400 x 1000, 1500 x 900, 1500 x 1000, 1600 x 1000, 1800 x 1000, 2000 x 1000mm

Angle Tray -- 900 x 900, 1000 x 1000

Custom sizes up to 2000mm available

ON-FLOOR TRAY

Installation onto timber or concrete floor. Threshold Height 50 / 60mm. Width 50mm

LEVEL-ENTRY TRAY (15mm step-down)

Installation onto rebated timber or concrete floor

WHEELCHAIR-ACCESS TRAY (Flush-entry tray / no step-down).
Installation onto rebated timber or concrete floor

- 25-Year Leakproof Guarantee. See Warranty Statement

EASY-CLEAN TRAP

Standard Position: Centre or corner. Custom position optional
'Dome-Chrome' top
40mm or 50mm outlet

FRAMELESS-GLASS ENCLOSURE

Imported Toughened-Glass. Thickness: 10mm
NZ Standard Compliant to AS / NZS 2208:1996
Standard Height -- 1950mm
Configurations: Full enclosure with door or 'Walk-in' panel-only
Glass installed onto top of tray threshold
Positioning on threshold dependent on tiled walls
Hinges: Chrome-on-brass. Self-centreing
Handle: Standard: Stainless-steel Round 'D'
Optional handles available
Glazing Channel -- Bright Chrome anodised finish

LIQUID-APPLIED WALL MEMBRANES

Supplied by tiler or waterproofing contractor

INSTALLATION

Tray to be installed with polymer-modified tile adhesive
Frameless-glass enclosure to be installed by experienced frameless-glass installer

Tile to be installed with recommended tile adhesives