

STILE STAINLESS SHOWER BASE / TRAY

- One-piece, 1.5mm thick. Brush-finished Stainless-steel
- Fibreglass-reinforced tray underside. Fully supported
- Corner or centre drain outlet
- STANDARD SIZES: 15
- CUSTOM SIZES AND DRAINOUTLET POSITION OPTIONAL
- Glazing channels: Bright-polished finish
Factory-installed to inside of tray
- Platinum 25-Year Leakproof Guarantee

ON-FLOOR TRAY

- Threshold height 60mm. Threshold width 50mm.
- 'Step-down' 15mm from top of the threshold into tray for optimum water containment
- Installation on timber or concrete floor.

LEVEL-ENTRY TRAY (15mm step-down)

- Installation onto rebated timber or concrete floor

WHEELCHAIR ACCESS TRAY (no step-down)

- Flush entry (no step-down) -- Installation onto rebated timber or concrete floor.

EASY-CLEAN TRAP

- Standard position: Tray rear or front corner or centre
- Custom position optional
- 'Dome-Chrome' top.
- Trap outlet pipe 40 / 50mm diameter
- Flow rate: 35 litres / min.
- Optional Hi-flow waste: Outlet 40 / 50mm diameter.
- Flow rate: 44 litres / min. (P or S-trap required)

FRAMELESS GLASS ENCLOSURE

- Thickness: 10mm toughened-glass.
- Standard Height: 2000mm. (Optional height)
- NZ Safety Standard compliant to AS/NZS 2206:1996
- Full enclosure with swing or sliding door or 'Walk-in' panel-only
- Hinges: Chrome-on-brass. Self-centring
- Handle: Polished Stainless-steel Round 'D'. (Optional handles)
- Tray glazing channel: Bright-finish. Factory-applied
- Wall glazing channel: Bright-finish
- Wall glazing channels applied directly to waterproofed walls

LIQUID APPLIED WALL MEMBRANES

- Supplied by tiler or waterproofing contractor.
See 'Recommended Waterproofing Membranes'

INSTALLATION

- Tray to be installed with polymer-modified tile adhesive.
- Frameless-glass enclosure to be installed by an experienced frameless-glass installer