



EASY-CLEAN TRAP / Hi-FLOW WASTE
AND STAINLESS-STEEL GRATE
SPECIFICATIONS
(Non-Corner Position on Tray)

DESCRIPTION

Easy-Clean Trap Side-Exit (as shown)

Optional: Bottom-Exit

Trap Seal: 75mm water seal

Flow Rate: 60-90 litres / min

Outlet Pipe Dia: 50mm

Trap Depth Below Tray: 120mm

Optional Use: Utilised as a Waste Fitting-only (internal seal-trap removed and 'waste-fitting' created is connected to floor-gully trap 50-100mm provided by plumber)

Optional: Bottom-Exit

Flow Rate: 90-100 litres / min

Depth Below Tray: 145mm

INSTALLATION

Fitted to Stile shower tray minimum 250mm from any corner

TILEABLE TOP

Tile adhered to top of trap / waste

Tileable Top height adjustable so as to be flush with tray tiles

Tile Dimensions: 100 x 100mm square

USE AS EASY-CLEAN TRAP

Requires periodic cleaning to remove any hair, soap, or body debris which may accumulate through normal useage. Left unattended any waste material may restrict water flow

USE AS WASTE-FITTING

Utilising a floor gully trap enhances water-flow capacity such that any hair, soap, body debris should pass through the connected floor gully trap without eventual buildup

MAINTENANCE

Do not use abrasive cleaners

Do not use solvent-based cleaning products

